

5 X 7 TCX0

• Industry standard footprint

Series **CTX7**






Part Numbering Example: CTX7SLZ-A3B3-15.360

CTX7	C	L	Z	A3	B3	15.360
SERIES	OUTPUT	VOLTAGE	PACKAGING OPTIONS	OPERATING TEMP.	STABILITY	FREQUENCY
CTX7	C=CMOS S=CLIPPED SINE	L=3.3V S=2.5V	Blank=Bulk Z=Tape and Reel	A1=-10°C ~ +50°C A2=-10°C ~ +60°C A3=-30°C ~ +75°C A4=-40°C ~ +75°C A7=-40°C ~ +85°C	B1=±5.0 ppm B2=±3.0 ppm B3=±2.5 ppm	

Specifications:

Frequency Range:	5.000 MHz to 52.000 MHz
Available Stability Options:	±5.0 ppm ±3.0 ppm ±2.5 ppm
Output Series:	Clipped Sine/CMOS
Input Voltage:	+5.0 VDC ±5% +3.3 VDC ±5%
Operating Temperature Range Options:	-10°C to +50°C -10°C to +60°C -30°C to +75°C -40°C to +75°C
Output Voltage:	1.0 Volt Peak to Peak Minimum
Frequency Trim Range With Externally Adjustable Trimmer:	± 3.0 ppm Minimum
Output Load:	10K OHM Parallel with 10 pf
Maximum Input Current:	2.0 mA
Maximum Frequency Aging at +25°C:	±1 ppm/yr
Freq. Stability Vs. Change of Input Voltage of ±5%:	±0.3 ppm
Packaging:	Tape and Reel (1K per Reel)

CTX7



PIN CONNECTION
 #1 V.C or N.C
 #2 GND
 #3 OutPut
 #4 Vcc

Recommended soldering pattern

